

LEXU II

„Low Exergy Wall & Air Tempering for Building Refurbishment“

>> **TRNSYS Experience Seminar 2018**

Belval (Luxembourg) 20.04.2018

M.Eng. Christoph Schmidt, IZES gGmbH, Saarbrücken
External doctoral student at the University of Luxembourg

Ein Projekt von

Research project LEXU II

External wall tempering

Motivation, contents und work packages

Research project LEXU II External wall tempering

Motivation, contents und work packages

„Refurbishment
„from the outside““

LowEx-Approach

*Utilization of low temperature
waste heat*

LEXU II:

❖ Outlying/external wall tempering (aWT): special case of TABS


1) Installation of panel heating/tempering „from the outside“

2) Installation of an ETICS (WDVS)

Position of the panel heating:

Inside of the thermal envelope of the building, outside of the existing wall, in front of the ETICS

→ Panel heating for existing buildings & thermal activation for the existing building structure



Details: „Außenliegende Wandtemperierung“ – LowEx-Anwendung zur Temperierung von Bestandsgebäuden und thermischen Aktivierung der Bestandswand: Theoretische Grundlagen und Kennwerte; Schmidt, C., Altgeld, Luther, Maas, Scholzen.; in Bauphysik 39 (2017), Heft 4, S.215-223

LEXU II:

❖ Advantages and disadvantages of the aWT

❖ Advantages:

- ❖ Thermal bridges / building damages
- ❖ Heating and cooling possible
- ❖ Increase of the inner surface temperature
→ *thermal comfort*
- ❖ Usage of very low fluid temperatures
→ LowEx
- ❖ Thermal activation of the existing building structure → storage
- ❖ Refurbishment „from the outside“ (without impairment for the inhabitants) → minimally invasive

❖ Disadvantages:

- ❖ Additional heat losses
→ Efficiency of the aWT
- ❖ Slow heating system.
 - ❖ → Focus: control strategies
 - ❖ → „base load heating“
- ❖ „New“ on-site build system:
 - ❖ „new“ and many interfaces
 - ❖ „new“ and many sources of error

Research project LEXU II

External air tempering

Motivation, contents und work packages

Research project LEXU II **External air tempering**

Motivation, contents and work packages


Refurbishment „from the outside“

Reducing of the heat load for
the aWT by tempering the
supply air with the aLT

*Reducing the (addtional) heat losses/
Increase of efficiency*

Fast system


External air tempering (aLT)



- 1) Existing wall
- 2) Active Layer
- 3) Air Gap
- 4) ETICS
- 5) Air inlet (hatch/filter)
- 6) Air outlet (hatch/filter)
- 7) Fan (Rohreinschub-)

External air tempering (aLT)

Exemplary comparison aWT – aLT (referred to 20°C room temperature):



Energetic advantages:

- The aLT (air) is like an additional heat transfer surface within the wall structure
- The efficiency can be increased by reducing the losses over the thermal insulation layer
- The importance of ventilation increases by an energetic refurbishment (higher tightness of the thermal envelope). By a combination of aWT & aLT the heat load can be completely covered

Positive control effects:

The slow adjustable aWT will be ideally or perfectly complemented by the quickly adjustable aLT.




→ Base Load + Peak Load possible.

LEXU II:

Modeling of the aLT in TRNSYS


- Energetic examination and futher simulations
(fluid dynamics simulation in ANSYS)



LEXU II:

Modeling of the aLT in TRNSYS: Two possibilities


Multi-zone (airnode) approach in Type 56



Conclusion:

Similar simulations results to Type 1230 and to the measurement results from the test wall; BUT very high input effort (up to 128 airnodes) and high error rate (lots of linkings) → no further considerations


Type 1230: Ventilated Facade (TESS)



Conclusion:

Less input effort. Division of the thermal envelope between Type 56 and Type 1230.
Tricky linking beetween Type 1230 and Type 56

Linking between Type 1230 und Type 56



TRNBuild: Zone XY / Airnode XY

Walls			
Surf	Type	Area	Category
2	IWAND_L	-	1.00 INTERNAL
4	AUSSENWAND_1230	-	1.00 BOUNDARY

+ -

Surface-ID: 4 Surface-ID: AUSSENWAND_1230

wall type: AUSSENWAND_1230

area: 1 m²

category: BOUNDARY

geosurf: 0

surf. gain inside: 0 kJ/h


coupling air flow: 0 kg/h

coulpl. rel. humidity: 0 %

boundary conditions: userdefined identical


1*T_1230

Linking between Type 1230 und Type 56



LEXU II:


Linking between Type 1230 und Type 56



LEXU II:

Linking between Type 1230 und Type 56

TRNBuild: Wall Type Manager



Definition of the resistive layer

Type 1230: Parameter

Parameter	Name	Value	Unit	More	Macro
6	Specific heat of wall material	0.9	kJ/kg.K	More...	<input checked="" type="checkbox"/>
7	Conductivity of wall material	0.13	kJ/hr.m.K	More...	<input checked="" type="checkbox"/>
8	Absorptance of exterior surface	0.6	-	More...	<input checked="" type="checkbox"/>
9	Emissivity of exterior surface	0.9	-	More...	<input checked="" type="checkbox"/>
10	Emissivity of inner surface	0.9	-	More...	<input checked="" type="checkbox"/>
11	Emissivity of back surface	0.9	-	More...	<input checked="" type="checkbox"/>
12	Resistance of back-side surface	0.01285	h.m ² .K/kJ	More...	<input checked="" type="checkbox"/>
13	Thickness of air gap	0.01	m	More...	<input checked="" type="checkbox"/>

Inverse

❖ Linking between Type 1230 und Type 56 (for the aLT)

Type 1230: Output

	Name	Value	Unit	More	Macro	Print
1	Air outlet temperature	10.0	C	More...	<input checked="" type="checkbox"/>	<input type="checkbox"/>
2	Air flow rate	0	kg/hr	More...	<input checked="" type="checkbox"/>	<input type="checkbox"/>
3	Exterior surface temperature	10.0	C	More...	<input checked="" type="checkbox"/>	<input type="checkbox"/>
4	Average wall temperature	10.0	C	More...	<input checked="" type="checkbox"/>	<input type="checkbox"/>
5	Average exterior air gap surface temperature	10.0	C	More...	<input checked="" type="checkbox"/>	<input type="checkbox"/>
6	Average air temperature	10.0	C	More...	<input checked="" type="checkbox"/>	<input type="checkbox"/>
7	Average interior air gap surface temperature	10.0	C	More...	<input checked="" type="checkbox"/>	<input type="checkbox"/>
8	Absorbed solar radiation	0	W/hr	More...	<input type="checkbox"/>	<input type="checkbox"/>

TRNBuild: Ventilation Type Manager

New Ventilation Type

"Ventilation Type" Manager

new ventilation type: TYPE1230

AirFlow

air change rate
 mass flow rate I: 1*M_ALT kg/h

Temperature of Air Flow

outside
 other I: 1*T_OUT_1230 °C



Humidity of Air Flow

relative humidity
 absolute humidity

outside
 other I: 1*RH_1230_OUT %

Verification of Type 1230

Comparison of an external wall with air layer (non ventilated) in Type 56 and Type 1230 + Type 56




LEXU II:

Verification of Type 1230

- ❖ Stationary conditions
- ❖ Transient conditions
- ❖ With/without irradiation
- ❖ Variation of the thickness of the air gap

Summary:


Differences <2% could be determined across all simulations and variations.



Model	T _{si} [°C]	T _{so} [°C]	Q _{si} [W]	Q _{so} [W]
Type 56	19,28	0,162	3,54	3,54
Type 56+ Type 1230	19,29	0,159	3,49	3,49

LEXU II:

Laboratory wall / test bench of the aLT




Nr.	Description	Thickness
1	Wood-fiberboard	18 mm
2	Insulation (Polystyrene)	160 mm
3	Wood-fiberboard	10 mm
4	Capillary tubes: active layer	10 mm
5	Air gap	20 mm
6	Insulation (Polystyrene)	160 mm
7	Wood-fiberboard	18 mm



Laboratory wall / test bench of the aLT

aLT-Laborwand




Measuring points:

- $T_{L,ein}$: Inlet temperature „air“ [°C]
- $T_{L,aus}$: Outlet temperature „air“ [°C]
- $T_{W,ein}$: Inlet temperature „water“ [°C]
- $T_{W,aus}$: Outlet temperature „water“ [°C]
- V_L : volume flow air [m^3/s]
- m_w : mass flow water [kg/min]

❖ Laboratory wall / test bench of the aLT

❖ Validation of Type 1230

- ❖ Comparison between measured data and simulation results
- ❖ Detailed evaluation and validation just in progress (>40 test series)
→ *Paper BauSim 2018, Karlsruhe (?)*



First Conclusion:

Good accordance of the measured data and the simulation results; differences ~5%

Documentation of a first validation for the aWT & aLT:

LEXU II – Einsatz von aussenliegender Wandtemperierung bei der Gebäudesanierung; Schmidt, C., Altgeld, Groß, Luther, Schmidt, D.; Proceedings of CESBP/BauSim 2016, Dresden

LEXU II: Demonstrator

❖ Building C 3.1 on the campus of „Universität des Saarlandes“

❖ Year of construction: 1969




Quelle: Google Maps, 2017




- ❖ **Western frontage**
- ❖ Height: ~15 m
- ❖ Width: ~13,5 m
- ❖ Area: ~200 m²
- ❖ 0,36 m ferroconcrete (Stahlbeton)

LEXU II: Demonstrator

- ❖ Detailed planning of the facade
- ❖ Idea: room-by-room control aWT + field test area aWT & aLT



- ❖ Kapillarrohrmatte „Optimat SB 20“
- ❖ Hersteller: Clina, Berlin
- ❖ Stammrohr: 20 x 2 mm
- ❖ Kapillarrohr 4,3 x 0,8 mm
- ❖ Abstand A: 20 mm
- ❖ Länge: 60-600 mm
- ❖ Breite: ab 150 mm
- ❖ → Fertigung der Matten passend
für die Fassade




Realization



Final step „Modeling of the aLT“: Validation of Type 1230 by a comparison with measured data from the field test area

LEXU II: Demonstrator

Hydraulic diagram „Demonstrator“



Questions?

Many thanks to the funding authority, our project partner and supporters!

Project management	Project partner	Supporter	Funding
 <p>Institut für ZukunftsEnergie- und Stoffstromsysteme</p>  <p>Großes entsteht immer im Kleinen.</p>	 <p>Kapillarrohrtechnologie für Heiz- und Kühlsysteme</p>  <p>KOMPETENZZENTRUM AUSBAU UND FASSADE</p>	 <p>UNIVERSITÄT DES SAARLANDES Referat FM: Facility Management</p>  <p>GEFGA Energiesysteme GmbH</p> <p>WIDAG GbR Dr. Gerhard Luther</p>	  <p>Gefördert durch:</p>  <p>Bundesministerium für Wirtschaft und Energie</p> <p>aufgrund eines Beschlusses des Deutschen Bundestages</p>